

SG REVOLUTION THE FORK TRUCK TYRE



Smooth



SM Pattern



C2 Pattern



S/C2 Pattern



S2/Y3 Pattern



C1 Pattern



C8 Pattern



Y2 Pattern



Y3 Pattern



Y5 Pattern



UC2 Pattern



LC2 Pattern

International Tyre & Wheel Solutions Limited

Sandringham Park | Lowton | Nr. Warrington | WA3 2QL

T/F: +44 (0)1942 677618 | M: +44 (0)7949 247309
Skype: les.williamsitwas | E: les@tyreandwheelsolutions.com
www.tyreandwheelsolutions.com

SG REVOLUTION THE FORK TRUCK TYRE

Tyre Size	Pattern	Rim Sizes	Diameter mm	Width mm	Weight kg	Load Capacity				
						Steering Wheels kg	Load Wheels kg	6 km/h	10 km/h	25km/h
1200-24	C2	8.50-24 & 9.00-24	1249	310	297	7800	9360	9360	8424	7800
1200-24	SC2	8.50-24 & 9.00-24	1180	288	258	7500	9000	9000	8100	7500
900-20	C1	7.00-20	964	223	115	4600	5520	5520	4968	4600
825-20	C1	7.00-20	961	220	113	5000	6000	6000	5400	5000
1200-20	C2	7.50-20 & 8.00-20	1151	300	262	7500	9000	9000	8100	7500
1000-20	C2 & Y5	(7") (7.5") (8") x 20	1014	237	149	6000	7200	7200	6480	6000
1100-20	S/C8	7.50-20 & 8.00-20	1040	250	163	6200	7440	7440	6696	6200
1200-20	S2C2	7.50-20 & 8.00-20	1102	273	202	7600	9120	9120	8208	7600
1100-20	S2C2	7.50-20 & 8.00-20	1102	273	202	6200	7440	7440	6696	6200
1000-20	SMOOTH	(7") (7.5") (8") x 20	1000	242	156	6200	7440	7440	6696	6200
800-16	C2	5.50-16	799	200	78	3500	4200	4200	3780	3500
8.25-16	C2 & SC2	5.50-16	830	210	86	4600	5520	5520	4968	4600
825-16	S2 Smooth	5.50-16	820	220	93	4600	5520	5520	4968	4600
750-16	S2C2.	550-16 & 600-16	799	200	78	3500	4200	4200	3780	3500
28*9-15	C1 & Y	7.00-15	719	213	61	3500	4200	4200	3780	3500
750-15	S/C2	5.50-15	754	180	68	3500	4200	4200	3780	3500
700-15	S/C2	5.50-15	754	186	65	3500	4200	4200	3780	3500
750-15	S/C2	6.00-15	754	200	73	3500	4200	4200	3780	3500
815-15	S/C2	7.00-15	718	225	60	3500	4200	4200	3780	3500
28*12.5-15	S/C2	9.75-15	724	300	95	5200	6240	6240	5616	5200
825-15	S/C2 & Y5	6.50-15	828	225	96	4600	5520	5520	4968	4600
300-15	S/C2 & Y5	8.00-15	731	271	111	5600	6720	6720	6048	5600
355/65-15	S2/C2	9.00-15	860	322	143	7000	8400	8400	7560	7000
250-15	S2C2 & Y	700-15 & 750-15	740	240	80	4500	5400	5400	4860	4500
450-12	C1	3.00-12	453	120	20	1700	2040	2040	1836	1700
825-12	C1	5.00-12	725	188	61	3450	4140	4140	3726	3450
27*10-12	C2 & Y	8.00-12	690	268	77	4700	5640	5640	5076	4700
700-12	S/C2 & Y5	5.00-12	664	174	46	2800	3360	3360	3024	2800
23X10-12	S2/Y3	8.00-12	570	204	44	3500	4200	4200	3780	3500
650-10	S/C2 & Y5	5.00-10	576	160	33	2500	3000	3000	2700	2500
650-10	S/C2 & Y5	5.50-10	592	175	38	2500	3000	3000	2700	2500
650-10	S/C2 & Y5	6.00-10	592	175	37	2500	3000	3000	2700	2500
23*9-10	S2/Y3	6.50-10	570	204	44	3000	3600	3600	3240	3000
23*9-10	Y	7.00-10	579	207	44	3000	3600	3600	3240	3000
200/50-10	Y2	7.00-10	452	194	23	2700	3240	3240	2916	2700
16x5-9	RIB 1	3.50-9 & 4.00-9	470	124	13	1500	1800	1800	1620	1500
600-9	S/C1 & Y5	4.00-9	534	143	25	1760	2112	2112	1901	1760
600-9	S/C1 & Y5	4.00-9	536	150	29	1760	2112	2112	1901	1760
600-9	S/C1 & Y5	4.00-9	536	150	26	1760	2112	2112	1901	1760
21*8-9	Y & S2/Y3	6.00-9	524	180	33	2700	3240	3240	2916	2700
500-8	C2	3.75-8	452	117	15	1300	1560	1560	1404	1300
16x6-8	C2	4.33-8	415	135	15	1200	1440	1440	1296	1200
400-8	RIB 1	3.00-8 & 3.75-8	416	100	11	900	1080	1080	972	900
500-8	S/C2	3.00-8	452	117	16	1300	1560	1560	1404	1300
18*7-8	S2/Y3	4.33-8	438	154	19	1800	2160	2160	1944	1800
400-8	SC2 & LC2	3.00-8 & 3.75-8	416	100	11	900	1080	1080	972	900
500-8	SM & Y5	3.00-8	452	117	17	1300	1560	1560	1404	1300
18*7-8	Y	4.33-8	446	167	22	1800	2160	2160	1944	1800
15*4-1/2-8	Y2	3.50-8	368	102	10	1200	1440	1440	1296	1200
300-5	U / C2	2.50-5	245	75	3	300	360	360	324	300
350-5	U / C2	3.00-5	299	102	6	400	480	480	432	400
400-4	RIB 1	2.50-4	300	96	6	820	984	984	886	820